Honda Brochure Back Cover

TECHNICAL SPECIFICATIONS

	PARAMETERS	MEASUREMENTS
BODY DIMENSIONS	Length	1955 mm
	Width	754 mm
	Height	1050 mm
	Wheel Base	1245 mm
	Ground Clearance	168 mm
	Kerb Weight	99 kg
	Seat Length	677 mm
	Seat Height	786 mm
	Fuel Tank Capacity	9 L
ENGINE	Туре	4 Stroke, SI Engine
	Displacement	98.98 cc
	Max Engine Output	5.43 kW @ 7500 rpm
	Max Torque	8.05 N-m @ 5000 rpm
	Fuel System	PGM- FI
	Bore X Stroke (mm)	47.000 X 57.049
	Compression Ratio	10.0: 1
	Starting Method	Self/Kick
	Clutch Type	Multiplate Wet Clutch
	No. of Gears	4
TYRES & BRAKES	Tyre Size & Type (Front)	2.75 - 17 41P, Tube Type
	Tyre Size & Type (Rear)	3.00 - 17 50P, Tube Type
	Brake Type & Size (Front)	Drum Type , 130mm
	Brake Type & Size (Rear)	Drum Type , 110mm
FRAME & SUSPENSION	Frame Type	Diamond Type
	Front Suspension	Telescopic
	Rear Suspension	Twin
ELECTRICALS	Battery	12V, 3.0Ah
	Head Lamp	Bulb Type





Black With Red

Black With Blue





Black With Green

Black With Gold



With Grey BOOK ONLINE NOW!



Dealer Stamp

- Product shown in the picture may vary from actual product available in the market.
- Accessories shown in the picture are not part of standard equipment.

Honda Motorcycle & Scooter India Pvt. Ltd., Registered Office: Plot No. 1, Sector - 03, IMT Manesar, Distt. Gurugram, (Haryana) - 122050, India; Website: www.honda2wheelersindia.com; Customer Care: customercare@honda2wheelersindia.com







Honda Brochure 05



COMFORT.





The Combi-Brake System with Equalizer reduces braking distance, so you can ride with confidence.



Superior suspension makes driving easy on all kinds of roads.

Longer & Comfortable Seat



Longer, comfortable seat and great ergonomics make even long journeys comfortable.

Easy Ground Touch & Optimum Seat Height



Easy ground touch and optimum seat height enhances your comfort.









Adding to the safety of the rider, it cuts off the ignition if the vehicle is put in gear when the side stand is engaged.



Light frame reduces the overall weight of the motorcycle which makes it easier to handle it. Durable and tough frame suited for variable road conditions and extremely convenient for carrying load.

Small Turning Radius



Effective in tight corners and narrow roads.

Strong Grab Rail



Makes the motorcycle elegant and practical.